



Model MWR Wireline Set Sleeve Valve Cement Retainers are used for secondary cementing operations. These drillable retainers set securely in any hardness casing. A ratchet lock ring stores the setting force in the retainer. The one piece packing element and metal back up rings combine for a superior seal. The case hardened, one piece slips virtually eliminate premature setting, yet can be easily drilled out. They are available for 4 1/2" through 20" casing.

- Sets securely in any hardness casing, including premium grades Ratchet lock rings secure dynamic setting force
- One piece packing element and rocker action metal back up rings combine for a superior seal
- Compact, easy running
- Can be set directly with Baker wireline setting tools
- Shear studs are Baker style and connect directly to the Baker Adjuster Sub
- These bridge plugs can be run directly on Baker Setting Sleeves and Adjuster Subs
- Crossovers are not required

Part Number	Casing OD	Casing Wt	Setting Range Min ID	Setting Range Max ID	Tool OD
CPS0359001	4 1/2	9.5-16.6	3.826	4.090	3.59
CPS0393001	5	11.5-20.8	4.156	4.560	3.93
CPS0431001	5 1/2	13-23	4.580	5.044	4.31
CPS0470001	5 3/4	14-26	4.890	5.290	4.70
CPS0537001	6 5/8	17-32	5.595	6.135	5.37
CPS0568001	7	17-35	6.004	6.538	5.68
CPS0631001	7 5/8	20-39	6.625	7.125	6.31
CPS0712001	8 5/8	24-49	7.511	8.097	7.12
CPS0812001	9 5/8	29.3-58.4	8.435	9.063	8.12
CPS0943001	10 3/4	32.75-60.7	9.660	10.192	9.43
CPS0994001	11 3/4	60-83	10.192	10.772	9.94
CPS1043001	11 3/4	38-60	10.772	11.150	10.43
CPS1188001	13 3/8	48-80.7	12.175	12.715	11.88
CPS1412001	16	65-118	14.576	15.250	14.12
CPS1837001	20	94-133	18.730	19.124	18.37

Suite 245, 6025 - 12th Street S.E., Calgary, Alberta, Canada T2H 2K1

Tel. # (403)-543-0350, Fax. # (403)-543-0351

<mailto:canam@canamservices.com>

www.canamservices.com