



Model MMB Tubing Set Bridge Plugs are used to isolate zones for temporary or permanent abandonment. These drillable Bridge Plugs set securely in any hardness casing. A ratchet lock ring stores the setting force in the Bridge Plug. The one piece packing element and metal back up rings combine for a superior seal. The case hardened, one piece slips virtually eliminate premature setting, yet can be easily drilled out. They are available for 4 1/2" through 16" casing.

- Sets securely in most casing, including many premium grades
- Ratchet lock rings secure dynamic setting force
- One piece packing element and rocker action metal back up rings combine for a superior seal
- Compact, easy running
- Pressure balanced sleeve valve is opened and closed by tubing manipulation from the surface for better control
- Set with Model MSB Mechanical Setting Tool
- These bridge plugs can be set on any standard baker style mechanical setting tool

Part Number	Casing OD	Casing Wt	Setting Range Min ID	Setting Range Max ID	Tool OD
CPS0359009	4 1/2	9.5-15.1	3.826	4.090	3.59
CPS0393009	5	11.5-20.8	4.156	4.560	3.93
CPS0431009	5 1/2	13-23	4.580	5.044	4.31
CPS0470009	5 3/4	14-26	4.890	5.290	4.70
CPS0537009	6 5/8	17-32	5.595	6.135	5.37
CPS0568009	7	17-35	6.004	6.538	5.68
CPS0631009	7 5/8	20-39	6.625	7.125	6.31
CPS0712009	8 5/8	24-49	7.511	8.097	7.12
CPS0812009	9 5/8	29.3-58.4	8.435	9.063	8.12
CPS0943009	10 3/4	32.75-60.7	9.660	10.192	9.43
CPS0994009	11 3/4	60-83	10.192	10.772	9.94
CPS1043009	11 3/4	38-60	10.772	11.150	10.43
CPS1188009	13 3/8	48-80.7	12.175	12.715	11.88
CPS1412009	16	65-118	14.576	15.250	14.12

Suite 245, 6025 - 12th Street S.E., Calgary, Alberta, Canada T2H 2K1

Tel. # (403)-543-0350, Fax. # (403)-543-0351

<mailto:canam@canamservices.com>

[www.canamservices.com](http://www.canamservices.com)