



## Pump Seating Nipple

Pump Seating Nipples - Pump seating nipples are furnished in 8" and 12" lengths and all standard sizes with upset or non-upset tubing threads which conform to API specifications.

Special threads may be ordered. Pump seating nipples are ordinarily furnished with tubing threads. Nipples with working barrel threads must be specified. V Threads are not recommended for lifting.



Pump Seating Nipple				
Normal Pipe Size*	O.D	I.D	Length and Weight	
			8"	12"
			Weight EA.	Weight EA.
2" O.D Special Thread	2.000"	1.480"	6-1/4	9
2" API Upset	2.625"	1.781"		6
2" Non-Upset	2.625"	1.781"		
2" Special Thread	2.625"	1.781"		
2-1/2" API Upset	3.125"	2.250"	8	12
2-1/2" API Upset	3.125"	2.280"	11	8
2-1/2" Non-Upset	3.125"	2.250"		
2-1/2" Special Thread	3.125"	2.250"		
3" API Upset	3.750"	2.750"		17

[www.canamservices.com](http://www.canamservices.com)

245, 6025-12<sup>th</sup> Street SE, Calgary, AB, Canada T2H 2K1

E-mail: [canam@canamservices.com](mailto:canam@canamservices.com)

Tel: 1(403) 543-0350, Fax: 1(403) 543-0351

