

Hinged Casing Spider 200/ 250 Ton 3" Taper

Hinged casing spiders and bushings are well suited to use where casing needs to be run through a rotary table or where no rotary table is in place. They can slip on the rig floor or be supported by cribbing. With our range of sizes they can be used with most sizes of casing. All bores, except the internal bore of the 8 5/8", are 3" per foot tapers to use UC-3 or other 3" taper slips. The 8 5/8" is 4" per foot taper to be used with API standard smaller slips. We build our Hinged Casing Spiders in either 200 ton or 250 ton ratings. They are all built of high quality alloy steel and are tested and certified to API 7K specifications. 200 AND 250 TON HINGED CASING SPIDER 13 3/8" TO 36" BUSHINGS FOR 200 OR 250 TON HINGED CASING SPIDER FROM 8 5/8" (4" TAPER), 9 5/8" TO 30" (3" TAPER)



Specifications

| Description | Weight (lbs) |
|---|------------------|
| 36" Hinged Casing Spider | 1100 |
| 30" Hinged Casing Spider | 1868 |
| 20" Hinged Casing Spider | 1614 |
| 13- 3/8" Hinged Casing Spider | 950 |
| Reducing Bushings 200/ 250 Ton Hinged Casing Spider | |
| Description | Weight |
| 30" x 16" | 980 |
| 30" x 18- 5/8" | 900 |
| 30" x 20" | 850 |
| 30" x 24" | 755 |
| 30" x 26" | 605 |
| 20" x 16" | 395 |
| 20" x 13-3/8" | 480 |
| 13-3/8" x 10-3/4" | 160 |
| 13-3/8" x 10- 3/4" | Taper Inside 240 |
| <i>Other sizes available on request</i> | |