

Manual Rotary Tongs

Type "C" Tong covers drill pipe or casing sizes from 2 3/8" through 10 3/4" OD and is mostly used on smaller rigs. The new rugged latch design makes the "C" Tong stronger than other models and also can be ordered with an optional 30 7/8" lever, where space is a problem. The tong is made from alloy steel, heat treated and magnetic particle inspected. All specifications are certified.

Type C Manual Tong 35,000 ft/lb



Type C Manual Tong 55,000 ft/lb



Type "B" Tong has established itself to be one of the best for toughness and durability and it is the most popular tong on the market, also can be ordered with an optional 36" lever. The tong is made from alloy steel, heat treated and magnetic particle inspected. Sizes range from 3 1/2" through 13 3/8" OD All steel specifications are certified.

Type B Casing Tong 25,000 ft/lb

Type "B" Casing Tong Head is designed to handle casing sizes from 13 3/8" through 30". The Tong Head is made from alloy steel, heat treated and magnetic particle inspected, torque rating is 25,000 FT/LBS. All steel specifications are certified.



Type DB Casing Tong 65,000 ft/lb



Type "DB" Tong covers drill pipe or casing sizes from 3 1/2" through 17" OD and like the "SDD" it has excellent durability, the tong is made from alloy steel, heat treated and magnetic particle inspected. All steel specifications are certified.

Type MS Manual Tong 6,500 ft/lb

Type "MS" Tong is ideal for drilling and tubing work. Also used for seismographic, shot hole and exploration drilling. Like all other tongs a 3 Jaw design permits the jaws a uniform contact around the pipe. Jaw sizes range from 1.900" through 6 1/8" OD. All steel specifications are certified



Type LF Manual Tong 14,000 ft/lb



Type "LF" Tong is designed for water well drilling, seismographic, mining and geothermal rigs. Made from alloy steel, heat treated and magnetic partial inspected. Sizes range from 2 3/8" through 7 1/4" OD. An additional hinge jaw is available for pipe sizes from 7 1/4" to 8 5/8" OD. All steel specifications are certified.

Type AAX Casing Tong 55,000 ft/lb

Type AAX Manual Tong (Web wilson type) is an essential tool in oil drilling operation to fasten or remove the screws of drill pipe and casing joint or coupling, It can be adjusted by changing latch lug jaws



Type H Casing Tong 80,000 ft/lb



Type "H" Tong is ideal for light drilling and tubing work. Also used for seismographic, shot hole and exploration drilling. Like all other tongs a 3 Jaw design permits the jaws a uniform contact around the pipe. Jaw sizes range from 1.900" through 6 1/8" OD. All Steel specifications are certified.

Type SDD Casing Tong 100,000 ft/lb

Type "SDD" Tong covers drill pipe or casing sizes from 4" through 17" OD and is rugged in design and allows the operator greater torque when needed. The tong is made from alloy steel, heat treated and magnetic particle inspected, and complies to API 7K.

