



~est. 1990
CANAM
 pipe & supply

Tubing Specifications

NOM SIZE	OUTSIDE IN	DIAMETER MM	NOM LB/FT	WT. T&C KG/M	WALL IN	THICKNESS MM	TYPE	METERS / TONNE
3/4	1.050	26.7	1.14	1.70	.0113	2.87	NUE	588.23
3/4	1.050	26.7	1.20	1.79	0.113	2.87	EUE	558.65
3/4	1.050	26.7	1.55	2.31	0.154	3.91	IEU	432.90
1	1.315	33.4	1.70	2.53	0.133	3.38	NUE	395.25
1	1.315	33.4	1.72	2.56	0.133	3.38	IJ	390.62
1	1.315	33.4	1.80	2.68	0.133	3.38	EUE	373.13
1	1.315	33.4	2.30	3.42	0.179	4.55	IEU	292.39
1-1/4	1.660	42.2	2.10	3.12	0.125	3.18	IJ	320.51
1-1/4	1.660	42.2	2.30	3.42	0.140	3.56	NUE	292.39
1-1/4	1.660	42.2	2.33	3.47	0.140	3.56	IJ	288.18
1-1/4	1.660	42.2	2.40	3.57	0.140	3.56	EUE	280.11
1-1/4	1.660	42.2	3.29	4.90	0.198	5.03	IEU	204.08
1-1/2	1.900	48.3	2.40	3.57	0.125	3.18	IJ	280.11
1-1/2	1.900	48.3	2.75	4.09	0.145	3.68	NUE	244.49
1-1/2	1.900	48.3	2.76	4.11	0.145	3.68	IJ	243.30
1-1/2	1.900	48.3	2.90	4.32	0.145	3.68	EUE	231.48
1-1/2	1.900	48.3	4.19	6.23	0.219	5.56	IEU	160.51
2	2-3/8	60.3	4.00	5.95	0.167	4.24	NUE	168.06
2	2-3/8	60.3	4.60	6.84	0.190	4.83	NUE	146.20
2	2-3/8	60.3	4.70	6.99	0.190	4.83	EUE	143.06
2	2-3/8	60.3	5.80	8.63	0.254	6.45	NUE	115.87
2	2-3/8	60.3	5.95	8.85	0.254	6.45	EUE	112.99
2-1/2	2-7/8	73.0	6.40	9.52	0.217	5.51	NUE	105.04
2-1/2	2-7/8	73.0	6.50	9.67	0.217	5.51	EUE	103.41
2-1/2	2-7/8	73.0	8.60	12.80	0.308	7.82	NUE	78.13
2-1/2	2-7/8	73.0	8.70	12.95	0.308	7.82	EUE	77.22
3	3-1/2	88.9	7.70	11.46	0.216	5.49	NUE	87.26
3	3-1/2	88.9	9.20	13.69	0.254	6.45	NUE	73.05
3	3-1/2	88.9	9.30	13.84	0.254	6.45	EUE	72.25
3	3-1/2	88.9	10.20	15.18	0.289	7.34	NUE	65.88
3	3-1/2	88.9	12.70	18.90	0.375	9.52	NUE	52.91
3	3-1/2	88.9	12.95	19.27	0.375	9.52	EUE	51.89
3-1/2	4	101.6	9.50	14.14	0.226	5.74	NUE	70.72
3-1/2	4	101.6	11.00	16.37	0.262	6.65	NUE	61.08
4	4-1/2	114.3	12.60	18.35	0.271	6.88	NUE	54.49
4	4-1/2	114.3	12.75	18.97	0.271	6.88	EUE	52.71



API Colour Codes

Grade	Coupling colour code	Pipe colour code for threaded and/or plain end	Grade	Coupling colour code	Pipe colour code for threaded and/or plain end
H40			L80 9CR		
J55 tubing			L80 13CR		
J55 casing			C90		
K55			T95		
N80 Type 1			C110		
N80 Q			P110		
R95			Q125		
L80 Type 1					