

S E R I E S C

SEALER DISCS

16-48" (406-1219mm)

Size	O.D	I.D	Bolt Circle	# Holes	Hole Dia	Thick	Weight	Part #
16"	15.875	8.750	11.000	8	0.50	0.750	4.50	91-3210-16
18"	17.875	10.875	12.750	8	0.50	0.750	5.20	91-3210-18
20"	20.000	10.875	13.500	12	0.50	0.875	8.40	91-3210-20
22"	22.000	10.875	13.500	12	0.50	0.875	10.90	91-3210-22
24"	24.125	14.125	16.500	14	0.50	1.000	13.00	91-3210-24
26"	26.125	14.125	16.500	14	0.50	1.000	16.50	91-3210-26
28"	28.250	16.125	19.500	16	0.50	1.125	20.60	91-3210-28
30"	30.250	16.125	19.500	16	0.50	1.125	25.10	91-3210-30
32"	32.375	20.125	24.000	24	0.50	1.250	27.40	91-3210-32
34"	34.375	20.125	23.000	18	0.50	1.250	33.10	91-3210-34
36"	36.500	22.125	25.000	22	0.50	1.375	39.50	91-3210-36
38"	38.500	22.125	27.000	24	0.50	1.375	46.50	91-3210-38
40"	40.625	22.125	26.000	24	0.50	1.375	54.40	91-3210-40
42"	42.625	24.125	30.000	24	0.50	1.500	63.10	91-3210-42
48"	48.875	32.125	36.000	24	0.50	1.750	80.90	91-3210-48

Apache discs can be used in both bi-directional and uni-directional applications, or in conjunction with Series C cups as sealing or guide discs. The dimensions, durometer or composition of the discs can be varied to meet any special requirements.



All Apache discs are manufactured from high quality polyurethane and are available with a variety of wear resistant additives. Apache has also developed a proprietary chemically-resistant urethane suited specifically for severe environments such as hydrogen sulphide gas.